

Advanced facilities coupled with knowledgeable and experienced staff provides optimum performance and ability to handle a wide variety of machining requirements.

CNC Machining Equipment

- 1 Hass VF-4SS-V Vertical Machining Center (3-Axis)**
 BT40 Taper, 12,000-rpm Spindle, 31 Tool Capacity, 1270×508×635 (mm).
 Rapid traverse 35.6m/min, Max Cutting 21.2m/min, Pointing Accuracy ±0.005 mm.



- 2 Hass VF-2SS-V Vertical Machining Center (3-Axis)**
 BT40 Taper, 12,000-rpm Spindle, 31 Tool Capacity, 762×406×508 (mm).
 Rapid traverse 35.6m/min, Max Cutting 21.2m/min, Pointing Accuracy ±0.005 mm.



- 1 Hass VF-2SS-V Vertical Machining Center (3+2 Axis)**
 BT40 Taper, 12,000-rpm Spindle, 31 Tool Capacity, 200×200×350 (mm).
 Rapid traverse 35.6m/min, Max Cutting 21.2m/min, Pointing Accuracy ±0.003 mm.



- 1 JINGDIAO JDGR400_A13S High-Speed Machining Center (5-Axis)**
 BT30 Taper, 24,000-rpm Spindle, 24 Tool Capacity, 450×700×400 (mm).
 Rotation Angle B/C -120°~90°/360°, Worktable Diameter Φ400 mm.
 Rapid traverse 15m/min, Max Cutting 10m/min, Pointing Accuracy ±0.002 mm



- 2 JINGDIAO JDVT600T_A15SH High-Speed Machining Center (3-Axis)**
 HSK-A50 Taper, 24,000-rpm Spindle, 18 Tool Capacity, 600×500×300 (mm).
 Rapid traverse 18m/min, Max Cutting 10m/min, Pointing Accuracy ±0.005 mm.



- 2 JINGDIAO JDVT600_A13S High-Speed Machining Center (3-Axis)**
 BT30 Taper, 24,000-rpm Spindle, 21 Tool Capacity, 600×400×350 (mm).
 Rapid traverse 15m/min, Max Cutting 15m/min, Pointing Accuracy ±0.005 mm.



- 1 JINGDIAO JDCT600E_A12 High-Speed Machining Center (3-Axis)**
 BT30 Taper, 20,000-rpm Spindle, 15 Tool Capacity, 600×500×420 (mm).
 Rapid traverse 15m/min, Max Cutting 10m/min, Pointing Accuracy ±0.005 mm.



- 4 JIRFINE VH-85 Vertical Machining Center (3-Axis)**
 BT40 Taper, 15,000-rpm Spindle, 24 Tool Capacity, 850×550×550 (mm).
 Rapid traverse 36m/min, Max Cutting 20m/min, Pointing Accuracy ±0.005 mm.

